

Safety Data Sheet



1. Identification of Substance & Company

Product

Product name Dricon Foundry Sand

Other names NA
Product code NA

HSNO approval HSR002545

Approval description Construction Products (Carcinogenic) Group Standard 2020

UN number Not allocated

Proper Shipping Name NA
Packaging group NA
Hazchem code NA

Uses Raw Material for fine plastering, paint and grouting products.

Foundry moulding and stone masons.

Company Details

Company Dricon, Firth Industries

Address 810 Great South Road PO Box 14534
Penrose Panmure

Auckland, 1060 Auckland, 1741
New Zealand New Zealand

 Telephone
 +64-9- 583 2121

 Website
 www.dricon.co.nz

Emergency Telephone Number: 0800-764 766

2. Hazard Identification

Approval

This product has been approved under the Hazardous Substances and New Organisms Act (HSNO, Approval HSR002545, Construction Products (Carcinogenic) Group Standard 2020). The substance has been classified as hazardous according to the criteria in the Hazardous Substances (Hazard Classification) Notice 2020.

GHS 7 Classes

Hazard Statement

Carcinogenicity cat 1 STOT RE cat 1

H350 - May cause cancer if inhaled (contains crystalline silica)

H372 - Causes damage to organs through prolonged or repeated exposure

if inhaled. (may cause silicosis and effects to the lungs).

SYMBOLS

DANGER



Other Classifications

There are no other classifications that are known to apply.

Precautionary Statements

Prevention P103 - Read label before use.

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P260 - Do not breathe dust.

P264 - Wash hands thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product. P281 - Use personal protective equipment as required.

Response P308+P313 - IF exposed or concerned: Get medical advice/ attention.

Storage P405 - Store locked up.

Disposal P501 - Dispose of contents/container in accordance with local/regional/national/international regulation.



Safety Data Sheet

3. Composition / Information on Ingredients

Component	CAS/ Identification	Conc (%)
Crystalline silica	14808-60-7	99%

This is a commercial product whose exact ratio of components may vary. Trace quantities of impurities are also likely.

4. First Aid

General Information

You should call the National Poisons Centre if you feel that you may have been harmed by this product. The number is 0800 764 766 (0800 POISON) (24 hr emergency service).

If medical advice is needed, have this SDS, product container or label at hand. If exposed or concerned: Get medical advice/attention.

Recommended first aid

facilities

Ready access to running water is recommended. Accessible eyewash is recommended

Exposure

Swallowed Do NOT induce vomiting. Give a glass of water to drink. Contact a doctor if

experiencing symptoms.

Eye contact If product gets in eyes, wash material from them with running water for several minutes.

If symptoms persist, seek medical advice.

Skin contact This product is non-irritating to skin. No further measures should be required.

Inhaled If coughing, dizziness or shortness of breath is experienced, remove the patient to fresh

air immediately. If patient is unconscious, place in the recovery position (on the side) for

transport and contact a doctor.

Advice to Doctor

Treat symptomatically. See Section 11 for information on potential long term health effects from exposure to very fine crystalline silica dust.

5. Firefighting Measures

Fire and explosion hazards:

Suitable extinguishing substances:

Unsuitable extinguishing

substances:

Unknown.

Not applicable.

Products of combustion: Product does not burn. Dust may form irritating atmosphere. Product will react

exothermically with water. Contaminated water wil be strongly alkaline. Product may

There are no specific risks for fire/explosion for this chemical. It is non-combustible.

decompose in a fire and produce toxic or corrosive fumes.

Protective equipment: Self-contained breathing apparatus. Safety boots, non-flammable overalls, gloves, hat

and eye protection.

Hazchem code: NA

6. Accidental Release Measures

Containment Emergency plans to manage any potential spills must be in place. Prevent spillage from

spreading or entering soil, waterways or drains.

Emergency procedures In the event of large spillage alert the fire brigade to location and give brief description of

hazard. Wear protective equipment to prevent respiratory exposure. Clear area of any unprotected personnel. Sweep up the solid. Avoid creating dust. If appropriate, use a

gentle water spray to wet material to minimise dust generation.

Clean-up method
Collect and seal in properly labelled containers or drums for disposal or recycling.
Sweep up and collect recoverable material into labelled containers for recycling or

Sweep up and collect recoverable material into labelled containers for recycling or salvage. This material may be suitable for approved landfill. Dispose of only in accord

with all regulations.

Precautions Wear protective equipment to prevent the inhalation of dusts. Work up wind or increase

ventilation.







7. Storage & Handling

Storage Handling Stable under normal use and storage conditions.

Keep exposure to dusts to a minimum, and minimise the quantities kept in work areas. Minimise dust generation and accumulation. See section 8 with regard to personal protective equipment requirements. Avoid skin and eye contact and inhalation of dust.

8. Exposure Controls / Personal Protective Equipment

Workplace Exposure Standards

A workplace exposure standard (WES) has not been established by WorkSafe NZ for this product. There is a general limit of 3mg/m³ for respirable particulates and 10mg/m³ for inhalable particulates when limits have not otherwise been established.

NZ Workplace	Ingredient	WES-TWA	WES-STEL
Exposure Stds	Crystalline Silica (all forms)	0.05mg/m³ (as respirable dust)	no data

Engineering Controls

In industrial situations, it is expected that employee exposure to hazardous substances will be controlled to a level as far below the WES as practicable by applying the hierarchy of control required by the Health and Safety at Work Act (2015) and the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016. Exposure can be reduced by process modification, use of local exhaust ventilation, capturing substances at the source, or other methods. If you believe air borne concentrations of mists, dusts or vapours are high, you are advised to modify processes or increase ventilation.

Personal Protective Equipment

General

Personal Protective Equipment (PPE) should not be used as the primary means of exposure protection, except in the event of an accident or emergency situation or where all other means of protection have proven to inadequate. Clean PPE after use or dispose of as appropriate. Store PPE for re-use in a clean place. Regular training on the correct use of PPE should be provided. In particular the correct fitting and use of respirators and where applicable the cleaning of respirators should be undertaken.

Eyes

Protective eyewear is not normally necessary when using this product. However, it always prudent to use protective eyewear if dust is likely.

Skin

Avoid repeated or prolonged skin contact. Wear overalls, rubber boots and impervious gloves. Replace frequently. Gloves should be checked for tears or holes before use. Remove protective clothing and wash exposed areas with soap and water prior to eating,

drinking or smoking. Wash contaminated clothing before re-use.

Respiratory



To prevent irritation a well fitted dust mask should be used (this is not recommended when exposure is close to the WES). A fine particulate half or full face respirator with an effective seal is recommended when airborne concentrations approach the WES (section 8). If sanding, grinding, crushing or cutting concrete, it is possible that the silica dust WES (0.01 mg/m³) will be exceeded hence a respirator will be required. If exposure to the concentrated aqueous solution, dust and mist is likely, a full face respirator with a particulate filter is recommended.

WES Additional Information

Air monitoring to measure the overall amount of silica dust created at various positions on the worksite and the maximum level of worker exposure (given the use of dust control methods, respirators and other measures) should be carried out on a regular bases or when new work methods or equipment is introduced. Air monitoring can be carried out by occupational hygienists or other trained personnel.

9. Physical & Chemical Properties

Appearance Very hard, fine grained particles, white, buff or pink in colour Odour no odour **Odour Threshold** no data pН no data Freezing/melting point ~1600°C 2230°C **Boiling Point Flashpoint** no data **Flammability** no data Upper & lower flammable limits no data Vapour pressure no data Vapour density no data



Safety Data Sheet

Specific gravity/density 1.5 Solubility no data Partition coefficient no data **Auto-ignition temperature** no data **Decomposition temperature** no data **Viscosity** no data Particle Characteristics no data

10. Stability & Reactivity

Stability Stable

Conditions to be avoided Containers should be kept closed in order to avoid contamination. Avoid the creation of

dust.

Incompatible groups None known Hazardous decomposition None known products

Hazardous reactions

None known

11. Toxicological Information

Summary

IF SWALLOWED: No adverse effects anticipated under normal use conditions.

IF IN EYES: Fine dust may cause irritation when in direct contact.

IF ON SKIN: No adverse effects anticipated under normal use conditions.

IF INHALED: Short term (acute) silicosis can occur with one-off exposures to extremely high levels of fine crystalline silica dust. Other short term effects include irritation, choking and difficulty breathing.

CHRONIC EFFECTS: The dust does contain crystalline silica. Crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (IARC Group 1). The carcinogenicity of silica is related to long term (e.g., 10 years) inhalation of very fine particulate (e.g., from sand blasting or dry cutting of concrete). Carcinogenicity of silica appears linked to development of silicosis (see systematic below) followed by complications and, eventually lung cancer. In addition to silicosis there is some evidence that exposure to respirable crystalline silica may be linked to scleroderma and an increased risk of kidney disease.

Supporting Data

Eye

Acute Oral Not considered acutely toxic if swallowed.

Dermal Not considered acutely toxic by dermal contact.

Inhaled The substance is not considered acutely toxic if inhaled, however there may be irritation

of the respiratory tract if dust is inhaled. Short term (acute) silicosis (see "systemic" below) can also occur with one-off exposures to extremely high levels of fine crystalline silica dust. Other short term effects include irritation, choking and difficulty breathing.

The mixture is not considered to be an eye irritant. Dust may be an eye irritant

(mechanical irritation).

Skin The mixture is not considered to be a skin irritant.

Sensitisation No ingredient present at concentrations > 0.1% is considered a sensitizer. Chronic Mutagenicity No ingredient present at concentrations > 0.1% is considered a mutagen.

Carcinogenicity

The dust resulting from this product does contain crystalline silica. Crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to

humans (IARC Group 1). Crystalline Silica triggers carcinogenicity category 1

classification (confirmed carcinogen). The carcinogenicity of silica is related to long term (e.g., 10 years) inhalation of very fine particulate (e.g., from sand blasting or dry cutting of quartz containing substrates). Carcinogenicity of silica appears linked to development of

silicosis (see systematic below) followed by complications and, eventually lung cancer. No ingredient present at concentrations > 0.1% is considered a reproductive or

Reproductive / Developmental developmental toxicant or have any effects on or via lactation.

Systemic

The dust of this product is considered to be a target organ toxicant, because of the presence of crystalline silica at greater than 1%. Crystalline silica triggers STOT RE cat 1 classification if it is in the form of a fine respirable dust in an occupational (chronic exposure) setting. This is due to the development of silicosis which can occur following exposure to extremely high levels of fine silica dust. Silicosis is a type of pneumoconiosis a disease of the lung that causes inflammation, scar tissue, lesions and fibrosis in the lung (alveolar). Symptoms include shortness of breath, cough, fever, loss of appetite and cyanosis (bluish skin). Silicosis can occur following prolonged exposure (e.g., 10 years)

to relatively high levels of fine crystalline silica dust.

Persons with existing lung conditions may be at a higher risk of further adverse health Aggravation of existing conditions effects (as above). Smokers have an increased risk of lung cancer and silicosis.



Safety Data Sheet

12. Ecological Data

Summary

This mixture is not considered harmful or ecotoxic.

Supporting Data

Aquatic No evidence of aquatic toxicity for any of the ingredients present >1%.

Bioaccumulation No evidence of bioaccumulation

Degradability Not applicable.

Soil No evidence of soil toxicity.

Terrestrial vertebrateNot considered to be toxic towards terrestrial vertebrates **Terrestrial invertebrate**No evidence of toxicity towards terrestrial invertebrates.

Biocidal no data

13. Disposal Considerations

Restrictions There are no product-specific restrictions, however, local council and resource consent

conditions may apply, including requirements of trade waste consents.

Disposal method Disposal of this product must comply with the Hazardous Substances (Disposal) Notice

2017 and the requirements of the Resource Management Act for which approval should be sought from the Regional Authority. The substance must be treated and therefore

rendered non-hazardous before discharge to the environment.

Contaminated packaging Disposal of contaminated packaging must comply with the Hazardous Substances

(Disposal) Notice 2017 clause 12. Ensure that the package is rendered incapable of containing any substance and is disposed in a manner that is consistent with the requirements of the substance it contained and the material of the package. If possible

reuse or recycle packaging.

14. Transport Information

Land Transport Rule: Dangerous Goods 2005 - NZS 5433:2007

There are no specific restrictions for this product (not a dangerous good).

UN number: NA Proper shipping name: NA Class(es) NA Packing group: NA Precautions: NA Hazchem code: NA

IMDG

UN number: NA Proper shipping name: Not regulated

Class(es) NA Packing group: NA Precautions: NA EmS NA

IATA

UN number: NA Proper shipping name: Not regulated

Class(es)NAPacking group:NAPrecautions:NAERG GuideNA



Safety Data Sheet

15. Regulatory Information

This product is an approved substance under the Hazardous Substances and New Organisms Act (HSNO). Approval code: HSR002545: Construction Products (Carcinogenic) Group Standard 2020.

Specific Controls

Key workplace requirements are:

SDS To be available within 10 minutes in workplaces storing any quantity.

Inventory An inventory of all hazardous substances must be prepared and maintained.

Packaging All hazardous substances should be appropriately packaged including substances

that have been decanted, transferred or manufactured for own use or have been

supplied

Labelling Must comply with the Hazardous Substances (Labelling) Notice 2017.

Emergency plan Required if > 1000kg is stored.

Certified handler Not required.

Tracking Not required.

Bunding and secondary containment Mot required (non pooling substance) Signage Required if > 10000kg is stored.

Location compliance certificate Not required. Flammable zone Not required. Fire extinguisher Not required.

Note: The above workplace requirements apply if only this particular substance is present. The complete set of controls for a location will depend on the classification and total quantities of other substances present in that location.

Other Legislation

In New Zealand, the use of this product may come under the Resource Management Act and Regulations, the Health and Safety at Work Act 2015 and the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016, local Council Rules and Regional Council Plans.

16. Other Information

Abbreviations

Approval Code Approval Construction Products (Carcinogenic) Group Standard 2020, Controls, EPA.

www.epa.govt.nz

CAS Number Unique Chemical Abstracts Service Registry Number

ECotoxic Concentration 50% − concentration in water which is fatal to 50% of a test

population (e.g. daphnia, fish species)

EPA Environmental Protection Authority (New Zealand)

Globally Harmonised System of Classification and Labelling of Chemicals, 7th revised

edition, 2017, published by the United Nations.

HAZCHEM Code Emergency action code of numbers and letters that provide information to emergency

services, especially fire fighters

HSNO Hazardous Substances and New Organisms (Act and Regulations)

IARC International Agency for Research on Cancer

LEL Lower Explosive Limit

LD₅₀ Lethal Dose 50% – dose which is fatal to 50% of a test population (usually rats).

LC₅₀ Lethal Concentration 50% – concentration in air which is fatal to 50% of a test population

(usually rats)

NZIoC New Zealand Inventory of Chemicals

STEL Short Term Exposure Limit - The maximum airborne concentration of a chemical or

biological agent to which a worker may be exposed in any 15 minute period, provided the

TWA is not exceeded

STOT RESystem Target Organ Toxicity – Repeated Exposure
STOT SE
System Target Organ Toxicity – Single Exposure

Time Weighted Average – generally referred to WES averaged over typical work day

(usually 8 hours)

UELUpper Explosive LimitUN NumberUnited Nations Number

WES Workplace Exposure Standard - The airborne concentration of a biological or chemical

agent to which a worker may be exposed during work hours (usually 8 hours, 5 days a



Safety Data Sheet

week). The WES relates to exposure that has been measured by personal monitoring using procedures that gather air samples in the worker's breathing zone.

References

Data

Unless otherwise stated comes from the EPA HSNO chemical classification information

database (CCID).

Controls EPA notices, www.epa.govt.nz, Health and Safety at Work (Hazardous Substances)

Regulations 2017, www.legislation.govt.nz

WES The latest NZ Workplace Exposure Standards, published by WorkSafe NZ and available

on their web site – www.worksafe.govt.nz.

Other References: EU ECHA, ingredients SDS's, ChemIDplus

Review

DateReason for ReviewAugust 2023NA – new SDS

Disclaimer

This SDS was prepared by Datachem LTD and is based on our current state of knowledge, including information obtained from suppliers. The SDS is given in good faith and constitutes a guideline (not a guarantee of safety). The level of risk each substance poses is relevant to its properties (as summarised in the SDS) AND HOW THE SUBSTANCE IS USED. While guidelines are given for personal protective equipment, such precautions must be relevant to the use. The likely GHS 7 classifications, are based on our experience, EPA Guidelines and international classifications. A compliance record is available on request. This SDS is copyright Datachem and must not be copied, edited or used for other than intended purpose. To contact the SDS author, email info@datachem.co.nz or phone: +64 21 1040951.

